

# CBY

- Loading capacity from 2000kg to 5000kg
- Reliable and sturdy due to using strong high quality steel plate to make the fork



- Welding reinforcement bars on the back to further increase loading capacity.
- Powder-coated finish to ensure outer looking and prevent rusting.
- One-piece cast wheel frame with double front wheels guarantee maximum stability
- Outstanding galvanized whole casting hydraulic pump to ensure loading durability and prevent rusting.



- The dimensions of the chrome-plated piston rod are  $\phi 31.5\text{mm}$  for the 2T model,  $\phi 35\text{mm}$  for the 3T model and  $\phi 50\text{mm}$  for the 5T model.



- Nylon wheel: low drag efforts, high resistance to chemicals, non-marking, preferred in food, fishing and chemical industries with smooth floors



- PU wheel: Ideal for delicate floors with hard wearing and non-marking, quiet and durable



- Rubber wheel: Best choice for quiet and durable demands, ideal for smooth and rough floors

# CBY- 2T/2.5T/3T



Mental Handle



Rubber Wrapped Handle

Model	unit	CBY-2.0T (685*1220/550*1150)	CBY-2.5T (685*1220/550*1150)	CBY-3.0T (685*1220/550*1150)
Max. Load capacity	kg	2000	2500	3000
Max. lifting height	mm	195	195	195
Min. height of fork	mm	80	80	80
Overall Length	mm	1630/1560	1630/1560	1630/1560
Overall Width	mm	685/550	685/550	685/550
Fork dimension	mm	685*1220/550*1150	685*1220/550*1150	685*1220/550*1150
Pump Rod Diameter	mm	$\Phi 31.5$	$\Phi 35$	$\Phi 35$
Wheel type		Nylon/PU	Nylon/PU	Nylon/PU
Tyre size,drive	mm	$\Phi 180*50$	$\Phi 180*50$	$\Phi 180*50$
tyre size,load	mm	$\Phi 78x70$	$\Phi 78x70$	$\Phi 78x70$
Net Weight	kg	63/68	64/69	73/78